


M12: UC^{FUTURE} Patch Cord Style 3.0 mm Data Centre Cca Cable

ø3.0 mm, Class-C_{ca}, MPO patch cord cable with 12 fibres for data centers



Application and Installation

The intended application for this cable is MPO patch cords for data centres.

Fits to multi fibre connectors such as MPO® and MTP® connectors according to IEC 61754-7-1.

Standards

EN 50173-5, IEC 60794-2-20, ISO/IEC 24764

Flame Resistance

LSHF-FR (FRNC): IEC 60332-1-2; IEC 60332-3-24; IEC 60332-2-2; IEC 60754-1; IEC 60754-2; IEC 61034, EN 50399 Class-C_{ca}-s1a-d1-a1, Class D_{ca}; Class E_{ca}

Options

As an option this cable is available with 8 fibres.

Construction

Fibre	12 primary coated fibres, nominally 250 µm	
Fibre colours	1 Blue	7 Red
	2 Orange	8 Black
According to TIA/EIA 598-C also in agreement with IEC 60304	3 Green	9 Yellow
	4 Brown	10 Violet
	5 Grey	11 Pink
	6 White	12 Aqua
Strength member	Ultra high modulus Aramid yarns	
Sheath	FireRes® halogen free, flame resistant thermoplastic sheathing compound acc. to EN 50290-2-27, UV stabilised, 0.4 mm	
Sheath colours	Cable with BendBright ^{XS} SM fibres G.657.A2	Yellow, RAL 1018
	Cable with MaxCap-BB-OM3	Aqua, RAL 6027
	Cable with MaxCap-BB-OM4	Erika violet RAL 4003
	Cable with BendBright WideCap-OM5	Lime Green
Sheath Printing	DRAKA UCFUTURE FO I LBP M12 LSHF-FR Cca-s1a-d1-a1 <Fibre count> <Fibre type> <Fibre brand> <Item No> <Factory No> <Batch Number> <Meter mark>	

M12: UC^{FUTURE} Patch Cord Style 3.0 mm Data Centre Cca Cable

Physical Properties

Property	IEC 60794-1-21/22 Method	Value
Fibre count	-	8, 12
Nominal dimensions	-	3.0 mm ± 0.15 mm
Nominal weight [kg/km]	-	9
Tensile strength (dynamic)	E1	450 N (fibre strain ≤ 0.6%)
Tensile strength (permanent)	E1	225 N (fibre strain ≤ 0.2%)
Compressive strength (crush) (N/100mm)	E3	500N
Impact	E4	2 Nm, R= 12.5 mm
Torsion	E07	Pass
Kink	E10	No Kink
Min. Bending radius – permanent	E11	30 mm
Min. Bending radius – installation	E18a	60 mm
Temperature range	F12	Operation and installation: 0°C to 50°C. Storage: -20°C to 60°C

Product codes – ordering information

Product Code	DoP Number*	Product Description	Fibre Count	Fibre Type	Fibre Data Sheet
60072177	1007817	UC ^{FUTURE} FO I LBP LSHF-FR C 12 OM3B AQ	12	MaxCap-BB-OM3	C31
		UC ^{FUTURE} FO I LBP LSHF-FR C 8 OM4B 4003	8	MaxCap-BB-OM4	C32
60072179	1007819	UC ^{FUTURE} FO I LBP LSHF-FR C 12 OM4B 4003	12	MaxCap-BB-OM4	C32
		UC ^{FUTURE} FO I LBP LSHF-FR C 8 OM5B LG	8	WideCap-OM5	C39
		UC ^{FUTURE} FO I LBP LSHF-FR C 12 OM5B LG	12	WideCap-OM5	C39
60071129	1007552	UC ^{FUTURE} FO I LBP LSHF-FR C 12 SM7B YL	12	BendBright ^{XS} G.657.A2	C24
		UC ^{FUTURE} FO I LBP LSHF-FR C 12 SM7B.P YL	12	BendBright ^{XS} G.657.A2, tight geometry	C25
		UC ^{FUTURE} FO I LBP LSHF-FR C 12 SM7A1.P YL	12	BendBright ^{XS} G.657.A1, tight geometry	C38

*DoP Numbers are per product code and any DoP number proves CPR approval for the cable. DoP files can be downloaded from the website: www.prysmiangroup.com/cpr

© PRYSMIAN GROUP 2018, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.