

RG223 FRNC

RG-Cables acc. to MIL-C-17G



Application

see product overview

Standards

acc. to MIL-C-17F and MIL-C-17G

Flame resistance

acc. to IEC 60332-1

Construction

Inner conductor	copper wire, silver plated, diameter 0.90 ± 0.01 mm
Insulation	PE, diameter 2.95 ± 0.05
1 st braid	silver plated, 96% optical coverage
2 nd braid	silver plated, 96% optical coverage
Sheath	Flame Retardant Non Corrosive Copolymer, colour black RAL 9005, diameter 5.40 ± 0.10
Marking	DRAKA - M17/84 - RG223 FRNC <batch no.> <meter marking> m

Mechanical properties

Minimum bending radius	without load	5 x outer diameter
	with load	10 x outer diameter
Temperature	during operation	-40° C to + 85° C
	during installation	-15° C to + 55° C
Corrosivity of fire gases		acc. to IEC 60754-1 & 2
Smoke density		acc. to IEC 61034-1 and 2

All other requirements acc. to MIL-C-17G

Electrical properties

at 20°C

DC resistance	Inner conductor	29.1 Ω/km
	1 st braid	13.5 Ω/km
	2 nd braid	15.5 Ω/km
Mutual capacitance		100 pF/m
Characteristic impedance		$50 \Omega \pm 2 \Omega$
Velocity ratio		66 %
Max. operating frequency		12.4 GHz
Operating voltage		1.4 kV _{rms}
Test voltage	Inner/Outer conductor	5.0 kV _{rms}

RG223 FRNC

RG223 FRNC

Electrical data

at 20°C

Frequency (MHz)	Attenuation (dB/100m)	Max. power rating (Watts) (ambient temperature 25°C and max. inner conductor temperature 70°C)	Return loss (dB) several peaks are allowed	
			Frequency (MHz)	
	nominal	maximum		
50	9.8	350	100	≥ 27
400	28.4	86	1 GHz	≥ 23.5
1000	45.9	50	2 GHz	≥ 21.5
3000	83.1	32	4-5 GHz	≥ 21.0
5200	112.7	24	10 GHz	≥ 20
5800	120.6	22		

Technical data

Product code	Designation	Type	Brand name	Outer diameter	Weight	Standard delivery length	Drum size	Gross weight	Copper content	Tensile force
				mm	kg/km	m	*PWD	kg		
1002773 CK767650 0	2YCCH	0.89s/2.95Ds	M17/84-RG223 FRNC	5.4	56.2	1000	400/120/280	60	40.5	240

*PWD (plywood drum)

[PRODUCT CODE TABLE]

© PRYSMIAN GROUP 2010, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.