

# HD PRO 1.0/4.8 AF

## HD Video Cable 75 Ω



### Application

Video cables are primarily used in closed circuit TV systems and in several studio applications for transmission of image signals.

### Standards

For analogue and digital video signals (Composite, Component, SDI, SDV, SDTI, HDTV)

### Flame resistance

FRNC: IEC 60332-1; IEC 60754-2; IEC 61034

### Construction

Inner conductor	solid copper wire, bare, diameter 1.0 mm
Insulation	Foam-PE, diameter 4.8 mm
Outer conductor	Al-PET-Al-foil under tinned copper braid, diameter 5.6 mm
Sheath	FRNC diameter 7.0 mm anthracite
Printing	<b>DRAKA</b> - HD PRO 1.0/4.8 AF - 75 Ω ± 1%

### Electrical properties

at 20°C

DC resistance	Inner conductor	22 Ω/km
	Outer conductor	7 Ω/km
Mutual capacitance		56 pF/m
Characteristic impedance		75 Ω ± 0.75 Ω
Velocity ratio		78 %
Screening factor		≥ 100 dB

# HD PRO 1.0/4.8 AF

## Electrical data

at 20°C

Attenuation (dB/100m)		Return loss (dB)	
Frequency (MHz)		Frequency (MHz)	
1	0.8	50 – 300	≥ 26
3	1.3	300 – 3000	≥ 22
5	1.6	3000 – 3500	≥ 18
10	2.1	3500 – 5000	≥ 15
30	3.5		
100	6.2		
200	8.9		
300	11.3		
500	14.8		
800	18.5		
1000	20.7		
1500	24.9		
2250	31.7		
3000	37.3		
3500	41.5		
4000	47.2		
4500	51.2		
5000	55.1		

## Technical data

Product code	Type	Weight kg/km	Standard delivery length m	Drum size KTG/ring	Copper content	Tensile force N	Bending radius mm	Storage
1014490	HD PRO 1.0/4.8 AF	69	1000	071	35	140	45	inside

[PRODUCT CODE TABLE]

© PRYSMIAN GROUP 2009, All Rights Reserved

All sizes and values without tolerances are reference values. Specifications are for product as supplied by Prysmian Group: any modification or alteration afterwards of product may give different result.

The information contained within this document must not be copied, reprinted or reproduced in any form, either wholly or in part, without the written consent of Prysmian Group. The information is believed to be correct at the time of issue. Prysmian Group reserves the right to amend this specification without prior notice. This specification is not contractually valid unless specifically authorised by Prysmian Group.